

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 808 073 A2

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:  
19.11.1997 Bulletin 1997/47

(51) Int. Cl.<sup>6</sup>: H04Q 7/38

(21) Application number: 97107253.3

(22) Date of filing: 02.05.1997

(84) Designated Contracting States:  
DE ES FI FR GB SE

(30) Priority: 17.05.1996 GB 9610328

(71) Applicant: MOTOROLA LTD  
Basingstoke, Hampshire RG22 4PD (GB)

(72) Inventors:  
• Whinnett, Nicholas  
75004 Paris (FR)  
• Robinson, William  
78860 Saint Nom la Breteche (FR)

• Gibbs, Jonathan  
Southampton Hants SO30 2UL (GB)  
• van den Heuvel, Anthony  
78120 Clairesfontaine (FR)

(74) Representative:  
Dearling, Bruce Clive et al  
Motorola European Intellectual Property  
Operations  
Midpoint,  
Alencon Link  
Basingstoke, Hampshire RG21 7PL (GB)

## (54) Method and apparatus for mobile radio system selection

(57) A method and apparatus enables selection a communication system when a user of a mobile unit is away from a home system to which it is registered. According to one novel aspect, the visited communication system broadcasts (402) a list of standardized type services including tariff information, which is used by the mobile unit to select a system. According to another novel aspect, the mobile initiates an outgoing call of a non-standardised type service by accessing (502) a candidate system and informing it of the location of the home network and desired service identifier. The candidate system obtains (504) the service information on this service from the home network, and then provides (546) a quotation for a required service. Also, a communication system according to the present invention minimises incoming call costs to the user wherein the home system polls (606) the communication systems within range of the mobile unit to select the best system to provide service.




FIG. 5

EP 0 808 073 A2

## Description

### Field of the Invention

The present invention relates to communication systems, and more particularly, to a method and apparatus for selecting a communication system.

### Background of the Invention

Where a number of wireless networks which offer similar service capabilities are available for public access in the same geographic area, it is desirable to promote efficient spectrum loading, minimal call costs to the user, and competition between network operators. This is true in the user's "home" area as well as when the user roams to other areas. Efficient spectrum utilisation is promoted because lightly loaded systems can attract customers towards it. Also, overloading of networks, particularly packet data networks, can be avoided. By selecting the operator providing the desired service and quality of service at the lowest cost, the call costs tend to be minimised for the user, at least for outgoing calls. Finally, having dynamic costing structures promotes competition.

For future communications systems it is anticipated that two classes of service may exist. The first is a limited set of standardised core services such as telephony. The second is a set of operator-specific services which may be created by an operator and which are quite specific to the operator's network. A user in a home network may normally subscribe to a preferred operator or set of operators which provide mobility management and which together provide the user's desired service mix. An emerging requirement of third generation systems is that users when roaming should be able to access the same service set, even if the visited systems do not normally provide all the services.

Accordingly, there is also a need for a method and apparatus for selecting a communication system to minimize tariff rates.

### Brief Description of the Drawings

FIG. 1 is a block diagram of a communication network according to the present invention;

FIG. 2 is a block diagram of a communication system of FIG. 1;

FIG. 3 is a block diagram of a transmitter adapted to operate according to the present invention with one or more systems of FIG. 1;

FIG. 4 is a flow chart showing the method of selecting a system to make an outgoing call according to the present invention;

FIG. 5 is a flow chart showing the method for making an outgoing call for non-standardised service types according to the present invention; and

FIG. 6 is a flow chart showing the method for receiving an incoming call according to the present

invention.

### Detailed Description of the Invention

The present invention is directed to a method and apparatus for selection a communication system when a user of a mobile unit is away from the home system to which it is registered. According to one aspect of the present invention, the visited communication system broadcasts a list of standardized type services including any associated information such as quality, and tariff information for these services. At call setup time, the mobile scans all available systems and chooses one based upon the broadcasted information. According to an alternate embodiment, the mobile initiates an outgoing call of a non-standardised type service. In this case, the mobile accesses a candidate system and informs it of the location of the home network and desired service identifier. The candidate system obtains the service information on this service from the home network, and then provides a quotation for a required service. Also, a method of minimising incoming call costs to the user is described wherein the home system polls the communication systems within range of the mobile unit to select the best system to provide service.

Referring to FIG. 1, a home system 102 having a plurality of base stations 104 is coupled to a communication network 106 via a fixed wire link 105. The communication network 106 is a wide area communication network including a wireline network. Generally, communication network 106 includes hubs 108 and 110 having various transmission paths, including transmit network path 112 and transmit network path 114. A candidate system 120 having a plurality of base stations 124 is coupled to the communication network 106 via the hub 110. A second candidate system 130 also having a plurality of base stations 134 is coupled to the hub 110 of the communication network 106. A mobile terminal 140 is adapted to communicate with the candidate systems 120, 130.

Turning now to FIG. 2, the home system 102 preferably includes a mobile switching centre (MSC) 202. The MSC 202 is coupled to a Visitor Location Register (VLR) 204 as well as a Home Location Register (HLR) 206. The MSC 202 is also coupled to a Visitor Service Creation Platform (V-SCP) 208 as well as a Home Service Creation Platform (H-SCP) 210. The V-SCP 208 receives a service definition from a second system from which the mobile terminal 140 is visiting, and transmits tariff information to the second system for an incoming call. The V-SCP 208 also transmits tariff information for an outgoing call to a plurality of base station controllers (BSC) 220. The V-SCP 208 also controls the MSC using the service definition. Each BSC 220 is coupled to a plurality of base stations 104 which is adapted to communicate with the mobile terminal 140. Although the diagram shows by way of example the home system, the diagram could apply equally to one of the candidate systems 120, 130.

The mobile terminal 140 (FIG. 3), such as a cellular radiotelephone or other wireless communication device, comprises an ASIC (Application Specific Integrated Circuit) 301, such as a CMOS ASIC available from Motorola, Inc., and a microprocessor 303, such as a 68HC11 microprocessor also available from Motorola, Inc., which combine to generate a necessary communication protocol for operating in the communication system. The microprocessor 303 uses RAM 305, EEPROM 307, and ROM 309, consolidated in one package 304, to execute the steps necessary to generate the protocol and to perform other functions for the mobile terminal 40, such as writing to a display 313, accepting information from a keypad 315, and controlling a frequency synthesizer 325. The ASIC 301 processes audio transformed by the audio circuitry 319 from a microphone 317 and to a speaker 321. Transmitter 323 transmits through an antenna 329 using carrier frequencies produced by the frequency synthesizer 325. Information received by the antenna 329 of the mobile terminal 140 enters the receiver 327 which demodulates the symbols comprising the message frame using the carrier frequencies from the frequency synthesizer 325. The mobile terminal 140 may optionally include a message receiver and storage device including digital signal processing means. The message receiver and storage device could be, for example, a digital answering machine or a paging receiver. While the circuitry of FIG. 2 shows an exemplary terminal, other circuitry could be employed within the scope of the present invention.

Referring to FIG. 4, in order to make an outgoing call of a standardised type service, the candidate visited system broadcasts a list of standardized type services including any associated information such as quality and tariff information for these services (step 402). The tariff information may be a function of destination (e.g. long distance tariff). The tariff information is updated from time to time by the operator based, for example, upon system loading, and may include an indication of the duration for which the current tariff is valid. At call setup time, the mobile terminal 140 scans all available systems (step 404) and chooses one which offers the required service at the lowest rate (step 406). Alternatively, the mobile terminal 140 could select a system based upon criteria other than the cost of service. The mobile terminal 140 registers with the selected system for the required service and establishes the call (step 408). Alternatively, the mobile terminal 140 may also perform a background task of scanning the system broadcasts between calls and building up a tariff map of preferred systems for each service to reduce call setup delays.

According to an alternative embodiment, instead of the candidate systems 120, 130 broadcasting tariff information (step 402), the mobile terminal 140 polls local candidate systems 120, 130 at call set up time by initially on outgoing call of non-standard type service and informing the candidate system 120, 130 of the required service (the desired service identifier), and any

additional information such as quality and destination, for example, the location of the home network 102. The polled candidate systems 120, 130 also respond with tariff information which is received by the mobile terminal 140 (step 404). The mobile terminal 140 then chooses the candidate system 120, 130 which offers the required service at the lowest rate (step 406), and registers with the candidate system 120, 130 which fulfils the above criteria for the required service, and subsequently places the call (step 408). The polling takes the form of individual accesses to the various candidate systems 120, 130. According to another alternative embodiment, the mobile terminal 140 "broadcasts" its requirements on a common access channel, and local candidate systems 120, 130 respond with tariff information using a multiple access scheme. This multiple access scheme may simply involve holding the tariff information on a downlink channel long enough that the mobile terminal 140 can read the offers of the candidate systems 120, 130.

Turning now to FIG. 5, broadcasts from the candidate systems 120, 130 are not possible because the service set is unlimited. In addition, the entire service definition may not be known to the mobile terminal 140 and therefore the potential candidate systems 120, 130 may have to interrogate the home service provider before they can quote a delivery charge.

Therefore, in order to initiate an outgoing call of a non-standardised type service, the mobile terminal 140 accesses one of the candidate systems 120, 130 and informs it of the location of the home network 102 and desired service identifier (step 502). The candidate system 120, 130 obtains the service information on this service from the H-SCP of the home network 102 (step 504), and then the V-SCP of the candidate system 120, 130 provides a quotation for a required service (step 506). The mobile terminal 140 then determines whether other candidate systems 120, 130 are available (step 508). If other candidate systems 120, 130 are available, the mobile terminal 140 accesses the candidate system 120, 130 (step 502). If no other candidate systems are available, the mobile terminal 140 selects the candidate system 120, 130 (step 510). The mobile terminal 140 then accesses the selected candidate system (step 512). Alternatively, the selection may be made by the home system.

In an alternate embodiment, the mobile terminal 140 accesses one of the candidate systems 120, 130 and provides it with a service definition for the desired service. The V-SCP of the candidate system 120, 130 then offers the mobile terminal 140 a rate. This is repeated for other candidate systems 120, 130. The mobile terminal 140 chooses the one which offers the required service at the lowest rate. In some cases, the candidate system 120, 130 may not be able to provide the desired service (for example, it may not have interconnection to a particular information database). In this case, a "no bid" indication may be given. For outgoing calls, the choice of transit network (i.e. long haul net-

work between candidate system 120, 130 and home system 102) will be made by the candidate system 120, 130, and the particular destination or region may impact the offered rate to the user. Therefore, destination information for the call will be necessary.

Turning now to FIG. 6, a method of receiving an incoming call whilst minimising incoming call costs to the user will now be described. This is useful where charges are levied on incoming calls when roaming, which is the case currently when roaming with GSM. The mobile terminal 140 registers to one of the candidate systems 120, 130 (step 602). The H-SCP of the home network 102 (or equivalent) receives an indication of the incoming call for the mobile terminal 140 (step 604), and poles candidate systems 120, 130 known to exist in the locality of the mobile terminal 140, including the current visited candidate system 120, 130 (step 606). This may require the HLR (or equivalent) to provide to the visited candidate system(s) 120, 130 information on the service definition, if the service is not of the standardised service type. Alternatively, the HLR may have stored previously arranged tariffs for different visited candidate systems 120, 130 and for different services.

If, within some time constraint, the HLR finds a system prepared to offer the service at a lower rate than the currently registered visited candidate system 120, 130, a short message is sent to the mobile terminal 140 via the currently registered candidate system 120, 130 which informs the mobile terminal 140 to try and find the system prepared to offer the service at the lower rate (step 608). The mobile terminal 140 may be informed of the control channel set of the candidate system(s) 120, 130. If the mobile terminal 140 is able to find the candidate system 120, 130 within a time constraint, then registration occurs (step 610) and the call is delivered via the new visited system (step 612). If no better rate is available on another visited candidate system 120, 130, the call is delivered on the original visited candidate system 120, 130. The choice made by the home system 102 will preferably include considerations of the costs of possible transit networks between home and visited systems.

According to the above embodiments, it is thus possible, provided that the services are available from the candidate systems, for a user of the mobile terminal to select and access a service not identical to or substantially identical to a service set provided by the home network of the user.

According to an alternate embodiment, the mobile initiates an outgoing call of a non-standardised type service by accessing a candidate system and informing it of the location of the home network and desired service identifier. The candidate system obtains the service information on this service from the home network, and then provides a quotation for a required service. While the specific implementations of the present invention are described above, variations and modifications could be made by one skilled in the art within the spirit and

scope of the present invention. The present invention should be limited only by the appended claims.

## Claims

1. A method for selecting a communication system of a plurality of communication systems visited by a mobile unit, said method comprising the steps of:

receiving at said mobile unit tariff information broadcast from said plurality of communication systems;  
comparing said tariff information; and  
selecting a communication system based upon said comparison of said broadcast tariff information.

2. A method as claimed in Claim 1, further including a step of broadcasting from said mobile unit requirements of said mobile unit on a common access channel of said plurality of communication systems.

3. A method as claimed in Claim 2, wherein said step of receiving at said mobile unit tariff information broadcast from said plurality of communication systems comprises receiving tariff information by way of a multiple access scheme.

4. A method as claimed in Claim 1, further including a step of polling local candidate systems during call set up.

5. A method as claimed in Claim 4, further including a step of providing to said plurality of communication systems of said mobile unit requirements of said mobile unit.

6. A method as claimed in Claim 1, further including a step of originating a call on said selected communication system.

7. A method for selecting a communications system comprising repeating the method steps of Claim 1 on a call-by-call basis.

8. A method of originating an outgoing call by a communication system visited by a mobile unit associated with a home system, said method comprising the steps of:

receiving a request from said mobile unit to access said communication system;  
obtaining a service definition of said mobile unit; and  
providing a quote for said service to said mobile unit.

9. A method as claimed in Claim 6, wherein said step of obtaining a service definition comprises obtain-

ing a service definition from said home system.

10. A method as claimed in Claim 6, wherein said step of obtaining a service definition comprises obtaining a service definition from said mobile unit. 5

11. A method as claimed in Claim 8 or 9, further including a step of receiving an origination request for service from said mobile unit. 10

12. A method as claimed in Claim 7, further including a step of establishing a call on said selected communication system.

13. A method of originating an outgoing call comprising repeating the method steps of Claim 8 on a call-by-call basis. 15

14. A method of transferring an incoming call made to a mobile unit associated with a home communication system to said mobile unit located in a visited communication system, said method comprising the steps of: 20

receiving an incoming call to said mobile unit at said home system;  
polling communication systems accessible to said mobile unit and providing a service description to determine offered tariffs;  
selecting a communication system; and  
instructing said mobile unit to receive said incoming call on said selected communication system. 25 30

15. A method of transferring an incoming call made to a mobile unit comprising repeating the method steps of Claim 14 on a call-by-call basis. 35

16. A mobile unit adapted to select a communication system of a plurality of communication systems available to provide service to said mobile unit, said mobile unit comprising: 40

a receiver for receiving tariff information broadcast from said plurality of communication systems; and  
a control circuit for comparing said tariff information and selecting a communication system based upon said comparison of said tariff information. 45 50

17. A mobile unit adapted to select a communication system according to Claim 16, wherein the receiver receives Tariff information the control circuit compares the tariff information and selects the communication system on a call-by-call basis. 55

18. A communication system adapted to connect an outgoing call originated by a mobile unit associated

with a home communication system, said communication system comprising:



a base station for receiving a request from said mobile unit to access said communication system;  
a visitor service creation platform adapted to obtain a service definition from said home communication system or from said mobile unit; and  
a mobile switching center coupled to said visitor service creation platform for providing a quote for service to said mobile unit.

19. A communications system according to Claim 18, wherein the request is received from the mobile unit, the service definition is obtained and the quote for service is provided on a call-by-call basis. 15

20. A communication system adapted to transfer an incoming call made to a mobile unit associated with a home communication system to said mobile unit located in a visited communication system, said communication system comprising: 20

a mobile switching center for receiving a request for a call;  
a visitor service creation platform coupled to said mobile switching center and adapted to obtain tariff information from other communication systems; and  
a base station coupled to said mobile switching center for providing instructions to said mobile unit to access a selected communication system. 25 30 35

21. A communications system according to Claim 20, wherein receiving the request for the call, obtaining tariff information and accessing of a selected communication system are provided on a call-by-call basis. 40






FIG. 3




FIG. 4




FIG. 5





FIG. 6





Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) EP 0 808 073 A3

(12) EUROPEAN PATENT APPLICATION

(88) Date of publication A3:  
26.08.1998 Bulletin 1998/35

(51) Int. Cl.<sup>6</sup>: H04Q 7/38

(43) Date of publication A2:  
19.11.1997 Bulletin 1997/47

(21) Application number: 97107253.3

(22) Date of filing: 02.05.1997

(84) Designated Contracting States:  
DE ES FI FR GB SE

(30) Priority: 17.05.1996 GB 9610328

(71) Applicant: MOTOROLA LTD  
Basingstoke, Hampshire RG22 4PD (GB)

(72) Inventors:  
• Whinnett, Nicholas  
75004 Paris (FR)  
• Robinson, William  
78860 Saint Nom la Breteche (FR)

• Gibbs, Jonathan  
Southampton Hants SO30 2UL (GB)  
• van den Heuvel, Anthony  
78120 Clairefontaine (FR)

(74) Representative:  
Ibbotson, Harold et al  
Motorola European Intellectual Property,  
Operations,  
Midpoint,  
Alencon Link  
Basingstoke, Hampshire RG21 7PL (GB)

(54) Method and apparatus for mobile radio system selection

(57) A method and apparatus enables selection a communication system when a user of a mobile unit is away from a home system to which it is registered. According to one novel aspect, the visited communication system broadcasts (402) a list of standardized type services including tariff information, which is used by the mobile unit to select a system. According to another novel aspect, the mobile initiates an outgoing call of a non-standardised type service by accessing (502) a candidate system and informing it of the location of the home network and desired service identifier. The candidate system obtains (504) the service information on this service from the home network, and then provides (546) a quotation for a required service. Also, a communication system according to the present invention minimises incoming call costs to the user wherein the home system polls (606) the communication systems within range of the mobile unit to select the best system to provide service.




FIG. 5

EP 0 808 073 A3



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 97 10 7253

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	WO 94 28683 A (BRITISH TELECOMM) 8 December 1994 * page 7, line 1 - page 8, line 8 * * page 10, line 33 - line 39 * * page 12, line 35 - page 13, line 9 *	1-21	H0407/38 H04M15/00
A	GB 2 294 844 A (MOTOROLA INC) 8 May 1996 * the whole document *	1-21	
A	US 5 473 630 A (PENZIAR ARNO A ET AL) 5 December 1995 * the whole document *	1-21	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			H04Q H04M
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 7 July 1998	Examiner Nygren, P
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03/82 (P04C01)